

WSS - 3 0 5

Product technical specification

WSS- 305 is for solvent-based coatings and ink systems, can greatly enhance surface slip and substrate wetting properties, excellent compatibility.

- Significantly improved slip
- Fluidity, anti-blocking
- High efficiency , high compatibility (minimize the risk of fogging)
- Good recoatability
- Minimal impact on the adhesion between layers
- Provide a smooth feel to the leather finish

Recommended Applications

- Wood and furniture coatings

Recommended amount

In the form of supply to the total formula: 0.05-0.3 %

- Car paint

Recommended amount

In the form of supply to the total formula: 0.03-0.2%

- Leather top coat based on polyurethane, acrylic resin and nitro system

Recommended amount

Based on the supply form to the total formula: 0.1-1.0%

Technical data

Appearance: transparent liquid

Active matter content : 100%

Viscosity, 25 degree : about 26 is 0 in mPas

Process Description

Pre-diluted or directly added to the paint in the form of supply

Pre-dilution with the recommended solvent will facilitate addition and mixing

chemical composition

Organosiloxane copolymer

package

- 25KG , plastic bucket
- 200 kg , iron drum

Storage stability

Store in unopened original packaging and use within 12 months from the date of

production .

Free samples or learn more:

Please contact: 006598831607 (Singapore) Mr. Yang